



Window Sticker

SUMMARY

[Retail] 2022 Chevrolet Silverado 1500 LTD (CK18753) 4WD Double Cab 147" Custom

MSRP:\$45,348.00

Interior: Jet Black, Cloth seat trim

Exterior 1:Summit White

Exterior 2:No colour has been selected.

Engine, 2.7L Turbo

Transmission, 8-speed automatic, electronically controlled

OPTIONS

CODE	MODEL	MSRP
CK18753	[Retail] 2022 Chevrolet Silverado 1500 LTD (CK18753) 4WD Double Cab 147" Custom	\$45,348.00
	OPTIONS	
1CX	Custom Preferred Equipment Group	\$0.00
AE7	Seats, front 40/20/40 split-bench	\$0.00
CGN	Chevytec spray-on bedliner, Black with Chevrolet logo	\$600.00
G80	Auto-locking rear differential	\$450.00
GAZ	Summit White	\$0.00
GU6	Rear axle, 3.42 ratio	\$0.00
H1T	Jet Black, Cloth seat trim	\$0.00
IOR	Audio System, Chevrolet Infotainment 3 System, 7" diagonal colour touchscreen, AM/FM stereo	\$0.00
L3B	Engine, 2.7L Turbo	\$0.00
MQE	Transmission, 8-speed automatic, electronically controlled	\$0.00
NZP	Wheels, 20" x 9" (50.8 cm x 22.9 cm) Bright Silver painted aluminum	\$0.00
QAB	Tires, 275/60R20 all-season, blackwall	\$0.00
R7C	Option/package discount	-\$1,000.00
SFE	LPO, Wheel locks, set of 4	\$80.00
SFZ	LPO, Black Bowtie Emblem, front	\$90.00
VQK	LPO, Moulded splash guards, Black	\$250.00
VXH	LPO, Assist steps, chromed tubular, 6" rectangular	\$875.00



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





Fordered air senditioning overing toy	\$400.00
 Federal air conditioning excise tax	\$100.00
SUBTOTAL	\$46,693.00
Adjustments Total	\$0.00
Vehicle Tax	\$100.00
Destination Charge	\$1,950.00
TOTAL PRICE	\$48,743.00

FUEL ECONOMY

Est City:13.9 L/100 km

Est Highway:12.0 L/100 km

Est Highway Cruising Range:757.92 km



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





Standard Equipment

Package	
	Trailering Package includes trailer hitch, 7-pin and 4-pin connectors and (CTT) Hitch Guidance
	Custom Value Package includes (PCX) Custom Convenience Package, (ZLA) Infotainment Package and (Z82) Trailering Package
	Custom Convenience Package includes (BTV) Remote Start with (UTJ) content theft alarm, (C49) rear-window defogger, (UF2) bed LED cargo area lighting and (QT5) EZ Lift power lock and release tailgate (Included and only available with (PDX) Custom Value Package.)
	Infotainment Package includes (U2K) SiriusXM and (UE1) OnStar (Included and only available with (PDX) Custom Value Package.)
Mechanical	
	Durabed, pickup bed
	Engine, 2.7L Turbo (310 hp [231 kW] @ 5600 rpm, 348 lb-ft of torque [471 Nm] @ 1500 rpm) (STD)
	Transmission, 8-speed automatic, electronically controlled with overdrive and tow/haul mode. Includes Cruise Grade Braking and Powertrain Grade Braking (STD)
	GVWR, 7000 lbs. (3175 kg) (Requires Crew Cab or Double Cab 4WD model and (L3B) 2.7L Turbo engine.)
	Rear axle, 3.42 ratio
	Automatic Stop/Start
	Transfer case, single speed electronic Autotrac with push button control (4WD models only)
	Four wheel drive
	Battery, heavy-duty 730 cold-cranking amps/80 Amp-hr, maintenance-free with rundown protection and retained accessory power
	Alternator, 220 amps
	Frame, fully-boxed, hydroformed front section
	Steering, Electric Power Steering (EPS) assist, rack-and-pinion
	Brakes, 4-wheel antilock, 4-wheel disc with DURALIFE rotors
	Brake lining wear indicator
	Capless Fuel Fill
	Exhaust, single outlet
Exterior	
	Wheels, 20" x 9" (50.8 cm x 22.9 cm) Bright Silver painted aluminum (STD)
	Tires, 275/60R20 all-season, blackwall (STD)
	Tire, spare 255/80R17SL all-season, blackwall



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





Exterior	
	Wheel, 17" x 8" (43.2 cm x 20.3 cm) full-size, steel spare
	Tire carrier lock, keyed cylinder lock that utilizes same key as ignition and door
	Bumper, front (Body-colour.)
	Bumper, rear (Body-colour.)
	CornerStep, rear bumper
	Recovery hooks, front, frame-mounted, Black
	Cargo tie downs (12), fixed rated at 500 lbs (226.8 kg) per corner
	Grille (Body colour bars with black mesh inserts.)
	Headlamps, halogen reflector with halogen Daytime Running Lamps
	Lamps, cargo area, cab mounted integrated with centre high mount stop lamp, with switch in bank on left side of steering wheel
	LED Cargo Area Lighting located in pickup bed, activated with switch on centre switch bank or key fob
	Taillamps, LED with signature
	Mirrors, outside heated power-adjustable
	Glass, deep-tinted
	Door handles, Black
	Tailgate and bed rail protection cap, top
	Tailgate, standard
	Tailgate, gate function manual with EZ Lift includes power lock and release
Entertainment	
	Audio System, Chevrolet Infotainment 3 System, 7" diagonal colour touchscreen, AM/FM stereo Additional features for compatible phones include: Bluetooth audio streaming for 2 active devices, voice command pass-through to phone, wired Apple CarPlay and Android Auto capable (STD)
	SiriusXM enjoy a Platinum Plan trial subscription with over 140+ channels including commercial-free music, plus sports, news and entertainment. Plus listening on the SiriusXM app, online and at home on compatible connected devices is included, so you'll hear the best SiriusXM has to offer, anywhere life takes you. Welcome to the world of SiriusXM. (If you decide to continue service after your trial, the subscription plan you choose will automatically renew thereafter and you will be charged according to your chosen payment method at then-current rates. Fees and taxes apply. See the SiriusXM Customer Agreement at www.siriusxm.ca for complete terms and how to cancel. All fees, content, features, and availability are subject to change.)
	Audio system feature, 6-speaker system
	Bluetooth for phone, connectivity to vehicle infotainment system
	Wi-Fi Hotspot capable (Terms and limitations apply. See onstar.ca or dealer for details.)



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





lutanian	
Interior	
	Seats, front 40/20/40 split-bench with covered armrest storage (STD)
	Seat trim, Cloth
	Seat adjuster, driver 4-way manual
	Seat adjuster, passenger 4-way manual
	Seat, rear 60/40 folding bench (folds up), 3-passenger (includes child seat top tether anchor)
	Floor covering, colour-keyed carpeting
	Floor mats, rubberized vinyl, front (Deleted when LPO floor liners are ordered.)
	Floor mats, rubberized-vinyl rear (Deleted when LPO floor liners are ordered.)
	Steering wheel, urethane
	Steering column, Tilt-Wheel, manual with wheel locking security feature
	Instrument cluster, 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure
	Driver Information Centre, 3.5" diagonal monochromatic display
	Exterior Temperature Display located in radio display
	Compass located in instrument cluster
	Rear Seat Reminder
	Window, power front, drivers express up/down
	Window, power front, passenger express down
	Windows, power rear, express down
	Door locks, power
	Remote Keyless Entry, with 2 transmitters
	Remote vehicle starter system
	Cruise control, electronic with set and resume speed, steering wheel-mounted
	Theft-deterrent system, unauthorized entry
	Power outlet, front auxiliary, 12-volt
	USB ports, 2 (first row) located on instrument panel
	Air conditioning, single-zone manual, semi-automatic
	Air vents, rear, heating/cooling
	Defogger, rear-window electric
	Mirror, inside rearview, manual tilt



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





Interior	
	Assist handles front A-pillar mounted for driver and passenger, rear B-pillar mounted
	Chevrolet Connected Access capable (Subject to terms. See onstar.ca or dealer for details.)
Safety-Mechanical	
	StabiliTrak, stability control system with Proactive Roll Avoidance and traction control, includes electronic trailer sway control and hill start assist
Safety-Exterior	
	Daytime Running Lamps with automatic exterior lamp control
Safety-Interior	
	Airbags, dual-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front and rear outboard seating positions; Includes front outboard Passenger Sensing System for frontal outboard passenger airbag
	OnStar and Chevrolet connected services capable (Terms and limitations apply. See onstar.ca or dealer for details.)
	Rear Vision Camera
	Hitch Guidance dynamic single line to aid in trailer alignment for hitching
	Teen Driver a configurable feature that lets you activate customizable vehicle settings associated with a key fob, to help encourage safe driving behaviour. It can limit certain available vehicle features, and it prevents certain safety systems from being turned off. An in-vehicle report card gives you information on driving habits and helps you to continue to coach your new driver
	Tire Pressure Monitoring System with Tire Fill Alert (does not apply to spare tire)
WARRANTY	
	Warranty Note: <<< Preliminary 2022 Warranty >>> Basic Years: 3 Basic Miles/km: 60,000 Drivetrain Years: 5 Drivetrain Miles/km: 100,000 Drivetrain Note: Certain Commercial and/or Government Fleet vehicles and 1500 LD Pickups with a 3.0L Duramax Turbo-Diesel Engine: 5 years/160,000 km Corrosion Years (Rust-Through): 6 Corrosion Years: 3 Corrosion Miles/km (Rust-Through): 160,000

Technical Specifications

Corrosion Miles/km: 60,000 Roadside Assistance Years: 5

Roadside Assistance Miles/km: 100,000

3.0L Duramax Turbo-Diesel Engine: 5 years/160,000 km



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.

Roadside Assistance Note: Certain Commercial and/or Government Fleet vehicles and 1500 LD Pickups with a





Powertrain Transmission Drivetrain Four Wheel Drive Trans Order Code MQE Trans Type 8 Trans Description Cont. Automatic Trans Description Cont. Again N/A First Gear Ratio (:1) 4.56 Second Gear Ratio (:1) 2.97 Third Gear Ratio (:1) 2.08 Fourth Gear Ratio (:1) 1.69 Fifth Gear Ratio (:1) 1.27 Sixth Gear Ratio (:1) 1.00 Reverse Ratio (:1) 3.82 Clutch Size Trans Power Take Off N/A N/A Final Drive Axle Ratio (:1) N/A Transfer Case Model Magna Transfer Case Gear Ratio (:1), High 1.00 Transfer Case Gear Ratio (:1), Low N/A Transfer Case Power Take Off N/A Seventh Gear Ratio (:1) 0.85 Eighth Gear Ratio (:1) 0.65 Mileage EnerGuide Estimate - City 13.9 L/100 km EnerGuide Estimate - Hwy 12.0 L/100 km Cruising Range - City 654.33 km Cruising Range - Hwy 757.92 km **Engine Engine Order Code** L3B **Engine Type** Turbocharged Gas I4 Displacement 2.7L/166 Fuel System **Direct Injection** 348 @ 1500 SAE Net Horsepower @ RPM 310 @ 5600 SAE Net Torque @ RPM Engine Oil Cooler N/A **Electrical** Cold Cranking Amps @ 0° F (Primary) Cold Cranking Amps @ 0° F (2nd) 730 N/A Maximum Alternator Capacity (amps) 220 Cold Cranking Amps @ 0° F (3rd) N/A **Cooling System Total Cooling System Capacity** N/A



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





, , , ,			
/ehicle			
Emissions			
Kg/yr of CO2 Emissions @ 20K km/year	N/A	G/km Of CO2 Emissions	306
Chassis			
Weight Information			
Standard Weight - Front	0 kg	Standard Weight - Rear	0 kg
Gross Axle Wt Rating - Front	1,723.68 kg	Gross Axle Wt Rating - Rear	1,723.68 kg
Curb Weight - Front	1,298.66 kg	Curb Weight - Rear	885.43 kg
Option Weight - Front	0 kg	Option Weight - Rear	0 kg
Reserve Axle Capacity - Front	425.02 kg	Reserve Axle Capacity - Rear	838.25 kg
As Spec'd Curb Weight	2,184.08 kg	As Spec'd Payload	991.12 kg
Maximum Payload Capacity	991.12 kg	Gross Combined Wt Rating	6,577.2 kg
Gross Axle Weight Rating	3,447.36 kg	Curb Weight	2,184.08 kg
Reserve Axle Capacity	1,263.28 kg	Total Option Weight	0 kg
Payload Weight Front	0 kg	Payload Weight Rear	0 kg
Gross Vehicle Weight Rating	3,175.2 kg		
Trailering			
Dead Weight Hitch - Max Trailer Wt.	2,268 kg	Dead Weight Hitch - Max Tongue Wt.	226.8 kg
Wt Distributing Hitch - Max Trailer Wt.	4,082.4 kg	Wt Distributing Hitch - Max Tongue Wt.	408.24 kg
Fifth Wheel Hitch - Max Trailer Wt.	4,037.04 kg	Maximum Trailering Capacity	4,082.4 kg
Fifth Wheel Hitch - Max Tongue Wt.	1,009.26 kg		
Frame			
Frame Type	Box Ladder	Sect Modulus Rails Only	N/A
Frame RBM	N/A	Frame Strength	N/A
Frame Thickness	N/A		
0			
Suspension			0 11 4 1
Suspension Type - Front	Independent	Suspension Type - Rear	Solid Axle
Spring Capacity - Front	1,723.68 kg	Spring Capacity - Rear	1,746.36 kg



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





nassis			
Suspension			
Axle Type - Front	N/A	Axle Type - Rear	N/A
Axle Capacity - Front	1,723.68 kg	Axle Capacity - Rear	1,723.68 kg
Axle Ratio (:1) - Front	3.42	Axle Ratio (:1) - Rear	3.42
Shock Absorber Diameter - Front	50.0 mm	Shock Absorber Diameter - Rear	50.0 mm
Stabilizer Bar Diameter - Front	33.02 mm	Stabilizer Bar Diameter - Rear	N/A
ires			
Front Tire Order Code	QAB	Rear Tire Order Code	QAB
Spare Tire Order Code	QAQ	Front Tire Size	275/60R20
Rear Tire Size	275/60R20	Spare Tire Size	255/80R17SL
Front Tire Capacity	1,723.68 kg	Rear Tire Capacity	1,723.68 kg
Spare Tire Capacity	N/A	Revolutions/Mile @ 45 mph - Front	N/A
Revolutions/Mile @ 45 mph - Rear	N/A	Revolutions/Mile @ 45 mph - Spare	N/A
Vheels			
Front Wheel Size	20" x 9" in	Rear Wheel Size	20" x 9" in
Spare Wheel Size	17" x 8" in	Front Wheel Material	Aluminum
Rear Wheel Material	Aluminum	Spare Wheel Material	N/A
Steering			
Steering Type	Electric Rack & Pinion	Steering Ratio (:1), On Centre	N/A
Steering Ratio (:1), At Lock	N/A	Turning Diameter - Curb to Curb	14.3 m
Turning Diameter - Wall to Wall	N/A		
rakes			
Brake Type	Pwr	Brake ABS System	4-Wheel
Brake ABS System (Second Line)	N/A	Disc - Front (Yes or)	Yes
Disc - Rear (Yes or)	Yes	Front Brake Rotor Diam x Thickness	342.9 x 29.97 n
Rear Brake Rotor Diam x Thickness	345.44 x 20.07 mm	Drum - Rear (Yes or)	N/A



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.





akes			
Rear Drum Diam x Width	N/A		
el Tank			
Fuel Tank Capacity, Approx	91 L	Aux Fuel Tank Capacity, Approx	N/A
Fuel Tank Location	N/A	Aux Fuel Tank Location	N/A
nensions			
erior Dimensions			
Passenger Capacity	6	Front Head Room	1,092.96 mm
Front Leg Room	1,131.06 mm	Front Shoulder Room	1,676.91 mm
Front Hip Room	1,553.97 mm	Second Head Room	1,012.95 mm
Second Leg Room	895.1 mm	Second Shoulder Room	1,647.95 mm
Second Hip Room	1,530.1 mm		
terior Dimensions	2.745.22	Langeth Overell w/a rear by many	NI/A
Wheelbase	3,745.23 mm	Length, Overall w/o rear bumper	N/A
Wheelbase Length, Overall	5,885.18 mm	Width, Max w/o mirrors	2,063.5 mm
Wheelbase Length, Overall Height, Overall	5,885.18 mm 1,921 mm	Width, Max w/o mirrors Overhang, Front	2,063.5 mm N/A
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper	5,885.18 mm 1,921 mm N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab	2,063.5 mm N/A N/A
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle	5,885.18 mm 1,921 mm N/A N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame	2,063.5 mm N/A N/A N/A
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor	5,885.18 mm 1,921 mm N/A N/A N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame	2,063.5 mm N/A N/A N/A N/A
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear	5,885.18 mm 1,921 mm N/A N/A N/A N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front	2,063.5 mm N/A N/A N/A N/A 205.23 mm
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear Ground Clearance, Rear	5,885.18 mm 1,921 mm N/A N/A N/A N/A N/A 205.23 mm	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame	2,063.5 mm N/A N/A N/A N/A
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear	5,885.18 mm 1,921 mm N/A N/A N/A N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front	2,063.5 mm N/A N/A N/A N/A 205.23 mm
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear Ground Clearance, Rear	5,885.18 mm 1,921 mm N/A N/A N/A N/A N/A 205.23 mm	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front	2,063.5 mm N/A N/A N/A N/A 205.23 mm
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear Ground Clearance, Rear Cab to Body	5,885.18 mm 1,921 mm N/A N/A N/A N/A N/A 205.23 mm	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front	2,063.5 mm N/A N/A N/A N/A 205.23 mm
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear Ground Clearance, Rear Cab to Body argo Area Dimensions	5,885.18 mm 1,921 mm N/A N/A N/A N/A N/A N/A N/A N/A 205.23 mm N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front Body Length	2,063.5 mm N/A N/A N/A N/A 205.23 mm 0 m
Wheelbase Length, Overall Height, Overall Overhang, Rear w/o bumper Cab to Axle Ground to Top of Load Floor Frame Width, Rear Ground Clearance, Rear Cab to Body argo Area Dimensions Cargo Box Length @ Floor	5,885.18 mm 1,921 mm N/A N/A N/A N/A N/A N/A 205.23 mm N/A	Width, Max w/o mirrors Overhang, Front Front Bumper to Back of Cab Cab to End of Frame Ground to Top of Frame Ground Clearance, Front Body Length Cargo Box Width @ Top, Rear	2,063.5 mm N/A N/A N/A N/A 205.23 mm 0 m



This document contains information considered Confidential between GM and its Clients uniquely. The information provided is not intended for public disclosure. Prices, specifications, and availability are subject to change without notice, and do not include certain fees, taxes and charges that may be required by law or vary by manufacturer or region. Performance figures are guidelines only, and actual performance may vary. Photos may not represent actual vehicles or exact configurations. Content based on report preparer's input is subject to the accuracy of the input provided. Data Version: 16690. Data Updated: 2-Nov-2021 11:35:00 PDT PM.